

高电位镁阳极			电流输出 (安培) / 土壤电阻率 (欧姆-厘米)												
型号/重量	长度 (cm)	直径 (cm)	500	1000	2000	2500	3000	4000	5000	10000	15000	20000	30000	40000	50000
3S3/ 3 lbs	16.5	15.2	0.37630	0.18815	0.09408	0.07526	0.06272	0.04704	0.03763	0.01882	0.01254	0.00941	0.00627	0.00470	0.00376
5S3/ 5 lbs	34.3	15.2	0.30527	0.15264	0.07632	0.06105	0.05088	0.03816	0.03053	0.01526	0.01018	0.00763	0.00509	0.00382	0.00305
9S2/ 9 lbs	78.7	12.7	0.38032	0.19016	0.09508	0.07606	0.06339	0.04754	0.03803	0.01902	0.01268	0.00951	0.00634	0.00475	0.00380
9S3/ 9 lbs	43.2	15.2	0.32249	0.16125	0.08062	0.06450	0.05375	0.04031	0.03225	0.01612	0.01075	0.00806	0.00537	0.00403	0.00322
17S2/ 17 lbs	139.7	12.7	0.53595	0.26798	0.13399	0.10719	0.08933	0.06699	0.05360	0.02680	0.01787	0.01340	0.00893	0.00670	0.00536
17S3/ 17 lbs	76.2	15.2	0.40730	0.20365	0.10182	0.08146	0.06788	0.05091	0.04073	0.02036	0.01358	0.01018	0.00679	0.00509	0.00407
20S2/ 20 lbs	158.8	12.7	0.58242	0.29121	0.14561	0.11648	0.09707	0.07280	0.05824	0.02912	0.01941	0.01456	0.00971	0.00728	0.00582
32S3/ 32 lbs	154.9	15.2	0.61104	0.30552	0.15276	0.12221	0.10184	0.07638	0.06110	0.03055	0.02037	0.01528	0.01018	0.00764	0.00611
32S5/ 32 lbs	76.2	20.3	0.47625	0.23812	0.11906	0.09525	0.07937	0.05953	0.04762	0.02381	0.01587	0.01191	0.00794	0.00595	0.00476
40S3/ 40 lbs	162.6	15.2	0.63012	0.31506	0.15753	0.12602	0.10502	0.07877	0.06301	0.03151	0.02100	0.01575	0.01050	0.00788	0.00630
48S5/ 48 lbs	86.4	20.3	0.50302	0.25151	0.12576	0.10060	0.08384	0.06288	0.05030	0.02515	0.01677	0.01258	0.00838	0.00629	0.00503
60S4/ 60 lbs	162.6	17.1	0.65825	0.32913	0.16456	0.13165	0.10971	0.08228	0.06583	0.03291	0.02194	0.01646	0.01097	0.00823	0.00658